


Quick-Lift Arm

QLA 35


***Ergonomic lifting
aid with unique
manoeuvrability
and flexible use***

Lifts up to 35 kg





QLA 35



Lifting capacity	Max 35 kg
Lift motor	Infinitely variable torque motor
Manoeuvring	Manoeuvring is done with KAHLMAN's patented manoeuvring handle. The handle is sensing the operator's hand/arm movement and gives a very exact and smooth speed control. Only a force equivalent to 20 gram is needed to engage the Up/down motion. When the operator let go of the handle, the up/down motion is immediately stopped.
Power supply	400-480V, 50-60 Hz, 3-phase + neutral and ground protection, 1, 9A
Stroke length	3,0 meter
Hinged arm	Constructed of painted aluminium profiles with a total length of 3.15 m. The position of the fixated lifting motor is carefully designed and tested to give optimum manoeuvrability of the hinged arm.
Suspension	Floor pillar in painted steel with a standard height of 3 m. Optional pillar heights up to 5 m depending on customers need. Also available is a wall or ceiling mounted bracket in painted steel.
Gripping device	Grippers are designed to fit customer's need. Intelligent I/O signals are available for optimum functionality.

Kahlman Produkter AB is not responsible or liable for any misinformation or incomplete information in publications and reserves the right to apply changes.



Zumpolle b.v. Montagetechnik

Molenstraat 4
5305 CH Zuilichem (NL)

tel +31 (0)418 - 671816 e-mail info@zumpolle.net
fax +31 (0)418 - 673217 web www.zumpolle.net